

Product Overview:

Introducing the Denon DN-C640, a fully specified Network Audio/CD player for use in all broadcast, installation and professional audio environments. The DN-C640 is a 1U rack-mount unit featuring a slot-load CD/DVD drive, able to read CDA, MP3, WMA, MP2 and PCM .wav files from CD or DVD media. It is also equipped with an inbuilt LAN port offering complete access to network audio files and remote control via a web based GUI.

With balanced, unbalanced, SP-DIF and AES outputs, an RS 232 port, an IR receiver and a parallel remote port, the DN-C640 fits into any and all pro audio environments requiring the playing of CD and the versatility of network audio selection, locally or remotely. Additionally the use of DVD media and compressed audio files can result in days of playback accommodating the most demanding of users.

The product is completed with a high visibility, fully featured fluorescent display and large backlit transport controls.

Key Features:

- Supports CD-DA (.cda), WAVE (.wav), MPEG-1/2 Layer III (.mp3), MPEG-1 Layer II (.mpg), Windows Media Audio (.wma)
- Slot in CD/DVD drive
- +/- 12% Pitch Control
- Quick Replay Feature
- End Monitor and User-selectable Finish Mode Features
- Cue to Music (with dedicated button)
- Program Play
- Balanced Audio Output
- Reads CD-R/RW, DVD-R/RW, and DVD+R/RW discs

<--->

MP3

- 1U/HE Rackmount Size

Applications:

- Broadcast
- Corporate Installation/BGM
- Fitness
- Retail & Leisure









DN-C640 Network CD Player



Further information:

Plays Back Digital Audio Existing on Other Network Devices

Not only can the DN-C640 decode a host of compressed and uncompressed digital audio files from CD or DVD data discs, but it now gives the end-user the unique ability to stream any of those files from a server or computer, as long as it is accessible via the network. Now, any corporate environment that records and stores their meetings on a network HDD or computer can simply navigate to that folder location from the front panel of the unit or by using the on-board web browser, select a specific file, and play it into their system. Any application from background music, to meeting recording playback, to small radio stations not utilising some sort of enterprise software to manage their station will benefit greatly from this unique feature.

Controllability for Every Application

The new Denon Professional DN-C640 comes with a host of control options, suitable for every application and every installation.

25-pin Contact Closure (GPIO)

Denon CD players have been used for years in the broadcast market and the DN-C640 is no exception. A 25-pin GPIO port allows for easy integration and full-featured usability in every broadcast studio or station installation.

9-pin RS-232C Control

The DN-C640 easily integrates into any new or existing installation using third-party serial control systems like Crestron® or AMX®.

IR Control with included IR Remote Control

Like most CD players, the DN-C640 is controllable by it's included IR commander. Perfect for small installations not using serial control solutions or Health and Fitness centers, the IR control allows every feature from playback to the +/-12% pitch control to be activated/adjusted.

Internal WEB GUI for Control from any Web-enabled Computer

It is becoming standard in our industry that any network device be controllable via a web-enabled computer. Because the machine has its own web server on-board, this means that any computer on the same network can call up and play audio files, build program playlists, and have full transport control functionality over the DN-C640.



www.dm-pro.eu/dnc640





Controls & Outputs: 10 11 12 13 14 2 ENON SFLAY А-В PITCH . . 6 ER ON/OFF NETWORK CD PLAYER DN-C640 DENON 0.7 0201 02:36:68 EJECT 0 disc LOCK END MON TEXT - INDEX/DIR + MENU/ST 3 5 CHE 1 4 SHIFT -PITCH-7 8 9 15 16 17 18 19 Front side key: Power switch A-B / End Mon button 16 Skip / back button 6 Display unit 11 1 2 Level control 7 Network button / indicator 12 Pitch button 17 Cue button 3 Headphone jack 8 Menu / Utility 13 Index / Dir / +/- button 18 Plpay / pause Shift button / indicator 4 DISC slot 9 14 Stop / cancel button 19 Jog wheel button 5 Eject Button 10 Display / lock button 15 Stop / cancel button AFO/FDI D&M HOLDINGS INC. PROFESSIONAL BUSINESS COMPANY 2-1 Nisshin-Cho, Kawasaki-ku, Kawasaki-shi, Kanagawa, Japan L 0 COMPLIES WITH FDA RADIATION PERFORMANCE STANDARDS,21CFR SUBCHAPTER J ALWAYS GROUND THE EQUIPM OBDA ALLTID UTRUSTNINGEN ORBIND ALTID UDSTYRE TC-20 0 0 FC AVIS;RISQUE DE CHOC ÉLECTRIQUE-NE PAS OUVRIR. Warning:Shock Hazard-do not open. ANALOG OUTPUT DIGITAL OUTPUT REMOTE LAN BALANCED R 6 8 4 5 7 9 3 EVEL ANALOG C 2 1 Rear side key: Unbalanced digital out jack Ethernet Balance out 4 6 Serial port 8 1 Output volume 5 Balanced digital out jack Parallel port 9 AC inlet 2 7 3 Unbalance out

www.dm-pro.eu/dnc640

DN-C640 Network CD Player

Specifications:

Dimensions Power supply Power consumption Dimensions excluding 19" rack kit Width Height Depth 19" rack kit height Weight

Audio Formats

Disc Type

Audio Formats Compatible Text

Inputs / Outputs LINE IN

Ethernet/LAN 1 - RJ-45 LINE OUT 2 Analog Unbalanced Outputs

1 Analog Balanced Output 2 Digital Outputs

1 Headphone Output

Control

RS-232 1 GPIO 1 Infrared 1 AC 100 - 240 V, 50/60 Hz 13 W

> 483mm 52mm 347mm 1U/HE 4.3kg

CD-DA, CD-R/RW, DVD-R/RW, DVD+R/RW cda, wav, mp3, mpg, wma CD-Text, ID3 v1/v2

Used for media playback over network

RCA L/R RCA L/R Variable Level XLR L/R Output with Trim Control RCA S/PDIF Format XLR AES/EBU Format w/LC 1 - 1/4" Headphone Output (front panel mounted)

> DB9 Bi-Directional connector DB25 Contact Closure IR receiver (front panel)



In the box:

- Power cable

- Phono cable (rca/cinch)

- User manual
- IR remote control



Dimensions & weight: (H x W x D): 2.04" x 19.01" x 13.66" (52mm x 483mm x 347mm) - 4.3kg, 1U/HE

www.dm-pro.eu/dnc640