

## PM58 / PM58S HIGH END VOCAL MICROPHONE

### GENERAL DESCRIPTION

PM58 / PM58S is a professional high end vocal microphone with high quality moving coil dynamic, high sensitivity, wide range frequency and wonderful polar pattern. Its shape is attractive and performance is excellent. The microphone adopts the die0case zinc alloy housing and strong head grill, which raise the resist falling capability of microphone in a way. The microphone uses in the theater performance as well as all kind of studio applications. Additional, PM58S has a switch to turn on or off the microphone.

### HOW TO USE MICROPHONE

#### PM58



PM58S's connect method is the same as this one.

## FEATURE

- \* High sensitivity, wide range frequency and wonderful polar pattern;
- \* Space-saving and light weight;
- \* Die-case zinc alloy housing, firm and durable;
- \* Applies to various occasions.

## CAUTION

- \* Do not disassemble , modify or attempt to repair the microphone;
- \* Do not store the microphone under direct sunlight, near heating devices or in a hot, humid or dusty place. Do not allow the microphone to get wet;
- \* When this product is used for a long time, the microphone may become discolored due to ultraviolet light (especially direct sunlight) or wear;
- \* To ensure compatibility and correct usage, always consult the user manual of any device before connecting the microphone to it;
- \* Do not subject the microphone to strong impact.

## SPECIFICATION

### PM58

- \* Microphone type: dynamic microphone
- \* Polar pattern: Cardioid
- \* Frequency response: 50Hz-13kHz
- \* Sensitivity: -55dB±3dB
- \* Output impedance: 370Ω±30%
- \* Net weight: 300g±20g

### PM58S

- \* Type: Dynamic
- \* Polar pattern: Cardioid
- \* Sensitivity: -51dB±3dB
- \* Frequency response: 50Hz-13kHz
- \* Net weight: 265g±20g
- \* Output impedance: 42Ω±30%

Copyright © Ningbo Yinzhou Alctron Electronics Co.,Ltd. All rights reserved. Specifications and appearance subject to change without notice.

ALCTRON ELECTRONICS CO.,LTD

No.76 SanCheng Road, XiuFeng Industrial Area,GaoQiao Town, NingBo China.

Tel:++86 574 87150672

Fax:++86 574 87157176

E-mail:info@alctron-audio.com

www.alctron-audio.com

## PM58/PM58S人声动圈话筒

### 产品介绍

PM58/PM58S是高品质动圈人声话筒，采用高品质的动圈音头，具有高灵敏度，宽频响，指向性佳等特点。本体采用压铸锌合金，强化网头，使得产品具有一定的抗跌落性。产品适合现场演出，也适用于各种录音场合。另外PM58S有一个开关来打开或者关闭麦克风。

### 如何使用麦克风

#### PM58



PM58S的连接方式同上。

## 特 征

- \* 高灵敏度，宽频响，指向性佳；
- \* 体积小，重量轻；
- \* 锌合金压铸壳身，坚固使用时间长；
- \* 使用范围广。

## ▲ 注意事项

- \* 请勿拆卸或改造麦克风；
- \* 不要将麦克风放在阳光直射下、暖气设备附近或湿热或多尘的地方。不要弄湿麦克风；
- \* 长时间使用本产品时，麦克风部分可能会因紫外线（特别是阳光直射）或磨损而变色；
- \* 为确保兼容及正确使用，在连接麦克风到任何装置之前，务必阅读装置的使用说明书；
- \* 请勿使麦克风受到强烈撞击。

## 参 数

### PM58

- \* 话筒类型： 动圈话筒
- \* 指向性： 心型
- \* 频率范围： 50Hz-13kHz
- \* 灵敏度： -55dB±3dB
- \* 输出阻抗： 370Ω±30%
- \* 净重： 300g±20g

### PM58S

- \* 话筒类型： 动圈式
- \* 指向性： 心型
- \* 灵敏度： -51dB±3dB
- \* 频响范围： 50Hz-13kHz
- \* 净重： 265g±20g
- \* 输出阻抗： 42Ω±30%

版权所有©奥创电子有限公司，所有权保留。必要的技术数据和外观更改不予以另外通知。

宁波市鄞州奥创电子有限公司

地址：浙江省宁波市鄞州区秀丰工业区三成路76号

电话：++86 574 88009874 传真：0574-87157176

邮箱：sales@alctron-audio.com 网址：http://www.alctron-audio.com

全国统一服务热线：4000-160-112